

TOPLOADER TL-K



**MAIN
APPLICATION AREAS:**

- Bulk material
- Maintenance organisations
- Repair shops
- Intermediate cleaning steps

Workplace implement



EQUIPMENT CHARACTERISTICS:

- All components in contact with fluid in stainless steel
- **Horizontally** rotating closed cage for bulk material
- Motor-driven cleaning cage
- High loading capacity (max. payload 50 kg)
- Siemens electrical equipment with Siemens Logo control
- High-efficiency high-power Grundfos pump IE3/IE4
- Dry running protection
- Tank cover

BUPI CLEANER® TOPLOADER TL-K

OVERALL DIMENSIONS APPROX.
(WITHOUT ADDITIONAL EQUIPMENT)

TL 80 K

Cleaning cage dimensions	471 x 321 x 200 mm
Width	1,220 mm
Depth	860 mm
Height with closed lid	1,030 mm
Payload	50 kg
Capacity tank	165 Litres
Spray pressure at nozzle mouth	3.2 bar
Circulation rate	12 m ³ /h
Pump motor	2.8 kW
Power electric heater	6.0 kW
Installed load	8.9 kW
Maximum current drain	10.5 A
Continuous treatment temperature control	0–85° C
Warm-up period tank from 15 to 70° C	approx. 2.5 hours



Information on accessories and
cleaning system configurator:
www.bupicleaner.com

