

## TOPLOADER TL



**MAIN  
APPLICATION AREAS:**

- Maintenance organisations
- Repair shops
- Intermediate cleaning steps

Workplace implement



**EQUIPMENT CHARACTERISTICS:**

- All components in contact with fluid in stainless steel
- **Vertically** rotating cage
- Motor-driven cleaning cage
- High loading capacity (max. payload 350 kg)
- Siemens electrical equipment with Siemens Logo control
- High-efficiency high-power Grundfos pumps IE3/IE4
- Dry running protection

## BUPI CLEANER® TOPLOADER TL

OVERALL DIMENSIONS APPROX. (WITHOUT ADDITIONAL EQUIPMENT)	TL 80	TL 100	TL 120
Wire basket, round	800 mm	1,000 mm	1,200 mm
Usable height	450 mm	500 mm	700 mm
Width	1,050 mm	1,280 mm	1,480 mm
Depth	900 mm	1,330 mm	1,530 mm
Height with closed lid	1,050 mm	1,200 mm	1,400 mm
Payload	150 kg	250 kg	350 kg
Capacity tank	120 l	300 l	430 l
Spray pressure at nozzle mouth	3.0 bar	3.5 bar	3.5 bar
Circulation rate	4.8 m <sup>3</sup> /h	12 m <sup>3</sup> /h	12 m <sup>3</sup> /h
Pump motor	0.85 kW	2.2 kW	2.2 kW
Power electric heater	4.5 kW	6.0 kW	9.0 kW
Installed load	6.0 kW	8.5 kW	11.5 kW
Maximum current drain	10.0 A	14.5 A	20.5 A
Continuous treatment temperature control	0–85° C	0–85° C	0–85° C
Warm-up period tank from 15 to 70° C	approx. 2.5 hours	approx. 2.5 hours	approx. 2.5 hours



Information on accessories and  
cleaning system configurator:

[www.bupicleaner.com](http://www.bupicleaner.com)

